

PARR 7313 ROOF FLASHING



Product Overview: PARR 7313, manufactured at the PARR facility, is a tacky rubber material formulated to meet AAMA Specification 820.1. This product features permanent resilience and elongation characteristics, as well as high levels of adhesion to a wide variety of substrates.

Product Uses: PARR 7313 is used for sealing roof seams on metal buildings, manufactured houses, and RV's. It weatherproofs all types of flashings and repairs roof blisters, cracks, gutters, copings, and parapet walls. PARR 7313 can also be used as an insulator, sound deadener, and anti-squeak agent in the assembly of metal components and vehicles.

Technical Information:

Raw Material Base.....	Synthetic Polymer Solids by Weight.....	100%
Cone Penetration.....	6.7 – 7.2 mm @ 77°F Heat Exposure 200°F.....	1200 hrs., No Effect
Color.....	Black Application Temp. Range.....	-20°F – 180°F
Specific Gravity.....	1.58 – 1.68 Shelf Life.....	18 Months
Elongation (ASTM D412).....	200% – 300% Manufactured State.....	Extruded Rolls
Flash Point.....	400°F Odor.....	Odorless
QUV Exposure.....	700 hrs., No Effect Peel Strength.....	2 pli @ 180°F, Al Foil
Water Absorption.....	24 hrs., 0.3% Water Vapor Transmission.....	0.0009 g/h · m ²
Oil Plasticizer Migration (ASTM C772).....	None Low Temp. Flexibility (ASTM C765).....	-45°F

Application Information: PARR 7313 material is extruded onto removable release paper backing to facilitate handling. For most efficient usage, it is recommended that the material be pressed onto one surface, stripped of its paper backing, and then brought into contact with the second surface. When lapping flash patches, allow at least a .25" gap. PARR 7313 can be painted on immediately with either water-based or oil-based paints.

Packaging & Handling: PARR 7313 is available in a variety of different widths, thicknesses, and roll dimensions. No special handling is required for this product, though storage in a cool, dry area is recommended for maximum shelf life and effectiveness.

Safety Instructions: No special requirements are needed. An MSDS is available upon request.

Contact Us: For more information regarding this product and others, please contact us at:

Edge Adhesives
3200 County Rd. 6 East
Elkhart, IN 46514
www.edgeadhesives.com

Toll Free: 1-866-476-PARR
Phone: 1-574-264-9614
Fax: 1-574- 262-9201

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Edge Adhesives control are such that Edge Adhesives assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.



5117 Northeast Parkway, Fort Worth, TX 76106
P. 817-232-2026 F. 817-847-5401
www.plioseal.com