

FLEECEBITE FLEECE REPAIR TAPE

Product Overview: FleeceBITE is a premium butyl tape, backed by a high-strength, stitch-bonded, fleece facer. This product is formulated to provide optimum levels of shear strength and tack. In addition, it is a permanently pressure-sensitive material that possesses excellent heat, water, and chemical resistance, and does not suffer any performance loss in extreme temperatures.

Product Uses: FleeceBITE is designed specifically for use in the metal building industry. It is commonly used to cover standing seams on metal roofs and decks prior to the application of acrylic and elastomeric roof coatings. FleeceBITE can also be used anywhere you have to bridge two dissimilar surfaces. The fleece backing allows for superior adhesion of coatings, sealants, mortar and stucco to the surface of the tape.

Technical Information:

Raw Material Base.....	Butyl Rubber	Solids Content (ASTM C771-74).....	100%
Adhesive Strength (ASTM D330).....	8 pli	Application Temp. Range.....	20°F – 150°F
Specific Gravity, Adhesive.....	1.4 – 1.5	Physical State.....	Solid
Standard Thickness (Adhesive).....	20 mil	Manufactured State.....	Extruded Roll
Elongation (ASTM D412, Adhesive).....	>500%	240°F Aging.....	No Change after 180 hrs.
Self Sealability (ASTM D1970).....	Passes	Color (Fleece).....	White
Service Temperature Range.....	-50°F – 300°F	Shelf Life.....	5 years

Application Information: All involved surfaces should be clean and dry. FleeceBITE is extruded onto release paper backing to facilitate handling. For most efficient usage, remove the release paper from the adhesive when preparing for use and handle only the fleece facer. Firmly press the material into place to ensure proper adhesion. Ensure that the application is free of contaminants and air entrapment. If involved surfaces are greasy, wipe with a light application of mineral spirits prior to installing FleeceBITE.

Packaging & Handling: FleeceBITE is sold in rolls that are fifty feet in length and available in 2, 3, 4, 6, 8, and 12 inch widths. No special handling is required for this product, though storage in a cool, dry area is recommended for maximum shelf life and effectiveness. Tools and equipment used while applying FleeceBITE can be cleaned using mineral spirits, if necessary.

Safety Instructions: No special requirements are needed. An MSDS is available upon request.

Contact Us: For more information regarding this product and others, please contact us at:

Edge Adhesives
5117 Northeast Parkway
Fort Worth, TX 76106

Phone: 817-232-2026
Fax: 817-847-5401
www.edgeadhesives.com

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Edge Adhesives control are such that Edge Adhesives assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.