

ISOCLEAN™

Cleaner for EPDM & other Single-Ply Membranes



TECHNICAL DATA



ISOCLEAN™ is a waterborne, high performance cleaner for hard-to-clean single-ply roof surfaces, such as weathered black EPDM. The proprietary formulation removes degraded surface rubber, making pressure washing much more effective, and thereby reducing labor necessary to prepare the roof surface for waterproofing with **ACRYLINK G™**.

The **ISOCLEAN™** application procedure is as follows:

- 1) Sweep off loose debris from area to be cleaned.
- 2) Stir Well.
- 3) Wet the surface with **ISOCLEAN™** at a rate of approximately 300-500 sq.ft. per gallon.
- 4) Keep the surface wet with regular water for 5-10 minutes.
- 5) After 1 minute of soaking, agitate the surface with a stiff bristle broom, power scrubber, etc.
- 6) After 5-10 minutes of soaking, thoroughly power-wash the roof.
- 7) Back-roll the first coat of **ACRYLINK G™**.

- ◆ Please refer to IPC's Technical Specifications Manual for detailed information on applying an **ACRYLINK G™** Roofing System.
- ◆ Please refer to the Material Safety Data Sheet for personal protection.



5117 Northeast Parkway, Fort Worth, TX 76106
P. 817-232-2026 F. 817-847-5401
www.plioseal.com

