

PLIOSEAL™ TAPE PRIMER PRIMER & SPLICE WASH

Product Overview: Plioseal Tape Primer is a specially designed, solvated primer formulated to prepare the surfaces of single-ply roofing membrane for adhesion with Plioseal tape products. In addition to surface preparation, Plioseal Tape Primer will also enhance the bonding strength between surfaces of seams and seals.

Product Uses: Plioseal Tape Primer is designed specifically for use in the EPDM roofing industry. However, it may be used with many other elastomeric roofing materials, as well as painted and unpainted metal, brick, ceramic, wood, vinyl, and concrete.

Technical Information:

Raw Material Base.....	Solvent	Solids Content (ASTM C771-74).....	3 – 7%
Visc., BRFLD RVT #2 @ 50 rpm.....	20 – 120 cps	Application Temp. Range.....	-15°F – 180°F
Specific Gravity.....	0.8 – 0.9	Physical State.....	Liquid
Pounds per Gallon.....	6.91	Manufactured State.....	Liquid
Flash Point, Seta Flash.....	<0°F	Color.....	Pale Amber
Application Temp. Range.....	>40°F	VOC.....	792.7 g/L

Application Information: Stir product before and during usage. Use Plioseal Tape Primer at full strength, do not dilute. Plioseal Tape Primer can serve as both a cleaner and primer for membrane surfaces in one operation. When this manner of application is desirable, saturate a clean pad with solvent and scrub it into the roofing membrane. When the pad becomes dirty, discard appropriately and use a fresh one. Once surfaces are dry to the touch, Plioseal tape products can then be applied for bonding purposes. Plioseal Tape Primer can also be applied by brush or lint-free cloth to membranes that have already been cleaned. This manner of application extends the estimated product coverage from 200 – 250 ft.² per gallon to 350 – 400 ft.² per gallon.

Packaging & Handling: Read all labeling before use. The recommended shelf life for Plioseal Tape Primer is nine months. To ensure maximum effectiveness, store this product indoors, out of direct sunlight, and at ambient temperatures of 60°F to 80°F. Always rotate stock. Plioseal Tape Primer is available in one gallon containers. Disposal of any material should be done so in accordance with local, state, and federal law. This product holds the following label requirement: DOT Flammable Liquid UN 1133.

Safety Instructions: WARNING! Plioseal Tape Primer contains high concentrations of toluene and xylene, solvents that are flammable in both liquid and vaporous states. Keep away from heat, spark, and open flame. Disconnect all gas and electrical appliances near work area. Use in a well ventilated area. Overexposure to vapors may cause dizziness, headache, and unconsciousness. Wear gloves and eye protection. Liquid product is an eye and skin irritant, and is harmful if swallowed. Consult Material Safety Data Sheet for further information.

Contact Us: For more information regarding this product and others, please contact us at:

Edge Adhesives
3709 Grove City Road
Grove City, OH 43123

Phone: 614-875-6343
Fax: 614-875-9041
www.edgeadhesives.com



Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Edge Adhesives control are such that Edge Adhesives assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.